


width \ length	1.65"		2.05"		2.2"		2.44"		2.67"		2.95"		3.15"		3.93"		4.92"															
	Pcs.	Vol. [mbf]	Pcs.	Vol. [mbf]	Pcs.	Vol. [mbf]	Pcs.	Vol. [mbf]	Pcs.	Vol. [mbf]	Pcs.	Vol. [mbf]	Pcs.	Vol. [mbf]	Pcs.	Vol. [mbf]	Pcs.	Vol. [mbf]														
118.11"	1000	1.44	840	1.44	800	1.48	720	1.48	640	1.44	600	1.48	560	1.48	440	1.44	320	-														
108.26"		1.31		1.31		1.35		1.35		1.31		1.35		1.35		1.31		1.35	1.35	1.35	1.31	1.35	1.31	1.22								
106.29"		1.27		1.27		1.27		1.27		1.27		1.31		1.22		1.27		1.22	1.27	1.27	1.27	1.27	1.27	1.14								
102.36"		1.18		1.18		1.18		1.22		1.18		1.22		1.18		1.14		1.18	1.18	1.18	1.18	1.18	1.18	1.1								
98.42"		1.14		1.14		1.14		1.14		1.14		1.18		1.14		1.14		1.14	1.14	1.14	1.14	1.14	1.14	1.05								
94.48"		1.1		1.1		1.1		1.1		1.1		1.14		1.1		1.1		1.1	1.1	1.14	1.14	1.14	1.1	1.01								
90.55"		1.1		1.1		1.1		1.1		1.1		1.1		1.14		1.1		1.05	1.1	1.1	1.1	1.1	1.1	0.97								
88.58"		1.1		1.1		1.1		1.1		1.1		1.1		1.1		1.1		1.05	1.1	1.1	1.1	1.1	1.1	0.97								
86.61"		1.05		1.05		1.05		1.05		1.1		1.1		1.1		1.1		1.05	1.1	1.1	1.1	1.1	1.05	0.97								
82.67"		1.01		1.01		1.01		1.01		1.01		1.01		1.01		1.01		1.01	1.01	1.05	1.01	1.01	1.01	0.93								
80.70"		0.97		0.97		0.97		0.97		1.01		1.01		1.01		1.01		0.97	1.01	1.01	1.01	1.01	0.97	0.88								
78.74"		0.97		0.97		0.97		0.97		0.97		0.97		0.97		0.97		0.97	0.97	0.97	0.97	0.97	0.97	0.88								
74.80"		1040		0.93		840		0.93		800		0.93		720		0.93		640	0.88	600	0.93	560	0.93	440	0.93	320	0.84					
70.86"				0.84				0.84				0.88				0.88			0.84		0.88		0.88		0.84		0.88	0.88	0.88	0.88	0.88	0.8
66.92"				0.8				0.8				0.8				0.84			0.8		0.84		0.8		0.8		0.84	0.8	0.84	0.8	0.84	0.8
62.99"	0.76		0.76	0.76	0.8		0.8	0.8	0.8		0.8	0.76	0.8		0.8	0.8	0.8		0.8		0.72											
59.05"	0.72		0.72	0.72	0.72		0.72	0.72	0.72		0.72	0.72	0.76		0.76	0.76	0.76		0.72		0.67											
55.11"	0.67		0.67	0.67	0.67		0.67	0.67	0.67		0.67	0.67	0.67		0.67	0.67	0.67		0.67		0.63											
51.18"	0.63		0.63	0.63	0.63		0.63	0.63	0.63		0.63	0.63	0.63		0.63	0.63	0.63		0.63		0.59											
47.24"	0.59		0.59	0.59	0.59		0.59	0.59	0.59		0.59	0.59	0.59		0.59	0.59	0.59		0.59		0.5											
43.30"	0.5		0.5	0.5	0.55		0.55	0.55	0.55		0.55	0.5	0.55		0.55	0.55	0.55		0.55		0.46											
39.37"	0.46		0.46	0.46	0.5		0.5	0.5	0.5		0.5	0.46	0.5		0.5	0.5	0.5		0.5		0.42											
37.40"	1040	0.46	840	0.46	800	0.46	720	0.46	640	0.46	600	0.46	560	0.46	440	0.46	320	0.42														
35.43"		0.42		0.42		0.42		0.42		0.42		0.42		0.42		0.42		0.42	0.42	0.42	0.42	0.42	0.42	0.38								
33.46"		0.42		0.42		0.42		0.42		0.42		0.42		0.42		0.42		0.42	0.42	0.42	0.42	0.42	0.42	0.38								
31.49"		0.38		0.38		0.38		0.38		0.38		0.38		0.38		0.38		0.38	0.38	0.38	0.38	0.38	0.38	0.33								
29.52"		0.38		0.38		0.38		0.38		0.38		0.38		0.38		0.38		0.33	0.38	0.38	0.38	0.38	0.38	0.33								
27.55"		0.33		0.33		0.33		0.33		0.33		0.33		0.33		0.33		0.33	0.33	0.33	0.33	0.33	0.33	0.29								
25.59"		0.29		0.29		0.29		0.29		0.29		0.29		0.29		0.29		0.29	0.29	0.29	0.29	0.29	0.29	0.29								
23.62"		0.29		0.29		0.29		0.29		0.29		0.29		0.29		0.29		0.29	0.29	0.29	0.29	0.29	0.29	0.25								
21.65"		2080		0.5		1680		0.5		1600		0.55		1440		0.55		1280	0.5	1200	0.55	1120	0.55	880	0.55	640	0.46					
19.68"	0.46		0.46	0.5	0.5		0.46	0.5	0.5		0.46	0.5	0.5		0.5	0.5	0.5		0.46													
17.71"	0.42		0.42	0.42	0.42		0.42	0.42	0.42		0.42	0.42	0.42		0.42	0.42	0.42		0.42		0.38											
15.74"	0.38		0.38	0.38	0.38		0.38	0.38	0.38		0.38	0.38	0.38		0.38	0.38	0.38		0.38		0.33											
13.77"	0.33		0.33	0.33	0.33		0.33	0.33	0.33		0.33	0.33	0.33		0.33	0.33	0.33		0.33		0.29											
11.81"	3120	0.46	2520	0.42	2400	0.42	2160	0.42	1920	0.42	1800	0.46	1680	0.42	1320	0.42	960	0.38														
9.84"		0.38		0.38		0.38		0.38		0.38		0.38		0.38		0.33		0.38	0.38	0.38	0.38	0.38	0.33									
7.87"		4160		0.38		3360		0.38		3200		0.38		2880		0.38		2560	0.38	2400	0.38	2240	0.38	1760	0.38	1280	0.33					



**Solid Beech:**  
**Tolerances:**  
**Thickness:**

Lightly steamed | Calibrated thickness | Homogeneous dried to 6-8 % KD | Cut-to-size after kiln drying  
 Thickness: calibration tolerance ± 0.012" | Width: ± 0.02" | Length: ± 0.012"/linear ft  
 0.94" (Invoiced thickness: 1.02")

The standard product limits hit-and-miss to about 1mm in thickness. A special sorting with hit-and-miss limit of 0.5 mm in thickness is available at request.