


width \ length	1.65"		2.05"		2.12"		2.2"		2.44"		2.67"		2.95"		3.15"		3.93"		4.92"	
	Pcs.	Vol. [mbf]	Pcs.	Vol. [mbf]	Pcs.	Vol. [mbf]	Pcs.	Vol. [mbf]	Pcs.	Vol. [mbf]	Pcs.	Vol. [mbf]	Pcs.	Vol. [mbf]	Pcs.	Vol. [mbf]	Pcs.	Vol. [mbf]	Stck.	Vol. [m³]
118.11"	1000	1.44	840	1.44	800	1.39	720	1.48	640	1.48	600	1.44	560	1.48	440	1.48	320	1.44	-	
108.26"		1.31		1.31		1.28		1.35		1.35		1.31		1.35		1.31		1.31		1.22
106.29"		1.27		1.27		1.26		1.27		1.31		1.22		1.27		1.27		1.27		1.14
102.36"		1.18		1.18		1.21		1.22		1.27		1.18		1.22		1.22		1.22		1.1
98.42"		1.14		1.14		1.16		1.18		1.22		1.14		1.18		1.18		1.14		1.05
94.48"		1.1		1.1		1.12		1.14		1.18		1.1		1.14		1.14		1.1		1.01
90.55"		1.1		1.1		1.07		1.1		1.14		1.05		1.1		1.1		1.1		0.97
88.58"		1.1		1.1		1.05		1.1		1.14		1.05		1.1		1.1		1.1		0.97
86.61"		1.05		1.05		1.02		1.1		1.1		1.05		1.1		1.05		1.05		0.97
82.67"		1.01		1.01		0.98		1.01		1.01		1.01		1.05		1.01		1.01		0.93
80.70"		0.97		0.97		0.95		1.01		1.01		0.97		1.01		1.01		0.97		0.88
78.74"		0.97		0.97		0.93		0.97		0.97		0.97		0.97		0.97		0.97		0.88
74.80"	1040	0.93	840	0.93	800	0.88	720	0.93	640	0.93	600	0.88	560	0.93	440	0.93	320	0.93	0.84	
70.86"		0.84		0.84		0.84		0.88		0.88		0.84		0.88		0.88		0.88		0.8
66.92"		0.8		0.8		0.79		0.84		0.84		0.8		0.84		0.84		0.84		0.76
62.99"		0.76		0.76		0.74		0.8		0.8		0.76		0.8		0.8		0.8		0.72
59.05"		0.72		0.72		0.70		0.72		0.72		0.72		0.76		0.72		0.72		0.67
55.11"		0.67		0.67		0.65		0.67		0.67		0.67		0.67		0.67		0.67		0.63
51.18"		0.63		0.63		0.60		0.63		0.63		0.63		0.63		0.63		0.63		0.59
47.24"		0.59		0.59		0.56		0.59		0.59		0.59		0.59		0.59		0.59		0.5
43.30"		0.5		0.5		0.51		0.55		0.55		0.5		0.55		0.55		0.55		0.46
39.37"		0.46		0.46		0.47		0.5		0.5		0.46		0.5		0.5		0.46		0.42
37.40"	1040	0.46	840	0.46	800	0.44	720	0.46	640	0.46	600	0.46	560	0.46	440	0.46	320	0.46	0.42	
35.43"		0.42		0.42		0.42		0.42		0.42		0.42		0.42		0.42		0.42		0.38
33.46"		0.42		0.42		0.39		0.42		0.42		0.42		0.42		0.42		0.42		0.38
31.49"		0.38		0.38		0.37		0.38		0.38		0.38		0.38		0.38		0.38		0.33
29.52"		0.38		0.38		0.35		0.38		0.38		0.33		0.33		0.33		0.33		0.33
27.55"		0.33		0.33		0.33		0.33		0.33		0.33		0.33		0.33		0.33		0.29
25.59"		0.29		0.29		0.30		0.33		0.33		0.33		0.33		0.33		0.33		0.29
23.62"		0.29		0.29		0.28		0.29		0.29		0.29		0.29		0.29		0.29		0.25
21.65"	2080	0.5	1680	0.5	1600	0.51	1440	0.55	1280	0.55	1200	0.5	1120	0.55	880	0.55	640	0.55	0.46	
19.68"		0.46		0.46		0.47		0.5		0.5		0.46		0.5		0.46		0.46		0.42
17.71"		0.42		0.42		0.42		0.42		0.42		0.42		0.46		0.42		0.42		0.38
15.74"		0.38		0.38		0.37		0.38		0.38		0.38		0.38		0.38		0.38		0.33
13.77"		0.33		0.33		0.33		0.33		0.33		0.33		0.33		0.33		0.33		0.29
11.81"	3120	0.46	2520	0.42	2400	0.42	2160	0.42	1920	0.42	1800	0.46	1680	0.42	1320	0.42	960	0.42	0.38	
9.84"		0.38		0.38		0.35		0.38		0.38		0.33		0.38		0.38		0.38		0.33
7.87"	4160	0.38	3360	0.38	3200	0.37	3200	0.38	2880	0.38	2560	0.38	2400	0.38	2240	0.38	1760	0.38	1280	0.33



Solid Beech:
Tolerances:
Thickness:

Lightly steamed | Homogeneous dried to 7-9 % KD | Calibrated thickness | Cut-to-size after kiln drying
 Thickness: ± 0.012" | Width: ± 0.02" | Length: ± 0.012" / linear ft
 0.94" (Invoiced thickness: 1.02")

The standard product limits hit-and-miss to about 0,04" in thickness. A special sorting with hit-and-miss limit of 0.019" in thickness is available at request.
www.pollmeier.com | tim@pollmeierusa.com | +1 501 868 9580