

length \ width	1.65" (42 mm)		1.77" (45 mm)		2.12" (54 mm)		2.67" (68 mm)		3.15" (80 mm)		3.93" (100 mm)		4.92" (125 mm)		
	Pieces	Vol. [mbf]	Pieces	Vol. [mbf]	Pieces	Vol. [mbf]									
<b>COMPONENTS</b>															
118.11" (3,000 mm)	1,000	1.36	960	1.40	800	1.40	640	1.41	560	1.45	440	1.42	320	1.29*	
108.26" (2,750 mm)		1.24		1.28		1.28		1.29		1.33		1.30		1.18	
94.48" (2,400 mm)		1.08		1.12		1.12		1.12		1.16		1.14		1.03	
88.58" (2,250 mm)		1.01		1.05		1.05		1.05		1.09		1.07		0.97	
86.61" (2,200 mm)		0.99		1.02		1.02		1.03		1.06		1.04		0.95	
82.67" (2,100 mm)		0.95		0.98		0.98		0.98		1.01		0.99		0.90	
78.74" (2,000 mm)		0.90		0.93		0.93		0.93		0.97		0.95		0.86	
74.80" (1,900 mm)	1,040	0.89	960	0.92	800	0.89	640	0.89	560	0.92	440	0.90	320	0.82	
70.86" (1,800 mm)		0.85		0.87		0.84		0.84		0.87		0.85		0.78	
62.99" (1,600 mm)		0.75		0.78		0.74		0.75		0.77		0.76		0.69	
59.05" (1,500 mm)		0.71		0.73		0.72		0.70		0.72		0.71		0.65	
55.11" (1,400 mm)		0.66		0.68		0.70		0.66		0.68		0.66		0.60	
51.18" (1,300 mm)		0.61		0.63		0.60		0.61		0.63		0.62		0.56	
47.24" (1,200 mm)		0.56		0.58		0.56		0.56		0.58		0.57		0.52	
39.37" (1,000 mm)	0.47	1,000	0.48	0.47	0.47	0.48	0.47	0.43							
35.43" (900 mm)	1,040	0.42	1,000	0.44	800	0.42	640	0.42	560	0.43	540	0.43	320	0.39	
31.49" (800 mm)		0.38		0.39		0.37		0.38		0.39		0.38		0.34	
29.52" (750 mm)		0.35		0.36		0.35		0.35		0.36		0.36		0.32	
27.55" (700 mm)		0.33		0.34		0.32		0.33		0.34		0.33		0.30	
25.59" (650 mm)		0.31		0.32		0.30		0.30		0.31		0.31		0.28	
23.62" (600 mm)		0.29		0.29		0.28		0.28		0.29		0.28		0.26	
21.65" (550 mm)		2,080		0.52		1,000		0.27		1,600		0.51		1,280	0.52
19.68" (500 mm)	0.47		0.24	0.47	0.47		0.48	0.47	0.43						
17.71" (450 mm)	0.42		0.22	0.42	0.42		0.43	0.43	0.39						
15.74" (400 mm)	0.38		2,000	0.39	0.37		0.38	0.38	0.34						
13.77" (350 mm)	0.33			0.34	0.33		0.33	0.34	0.33		0.30				
11.81" (300 mm)	0.42			0.44	0.42		0.42	0.43	0.43		0.39				
9.84" (250 mm)	3,120		0.35	3,000	0.36		2,400	0.35	1,920		0.35	1,680	0.36		1,320
7.87" (200 mm)	4,160	0.38	4,000	0.39	3,200	0.37	2,560	0.38	2,240	0.39	1,760	0.38	1,280	0.34	
5.91" (150 mm)	5,200	0.35	5,000	0.36	4,000	0.35	3,200	0.35	2,800	0.36	2,200	0.36	1,600	0.32	

COMPONENTS SORTED-TO-LENGTHS

106.34" - 118.11" (2.701 - 3.000 mm)	1,000	1.29	960	1.33	800	1.33	600	1.34	560	1.38	440	1.35	320	1.23
94.53" - 106.30" (2.401 - 2.700 mm)		1.15		1.19		1.19		1.20		1.23		1.21		1.10
82.72" - 94.49" (2.101 - 2.400 mm)		1.02		1.05		1.05		1.05		1.09		1.07		0.97
70.91" - 82.67" (1.801 - 2.100 mm)		0.88		0.91		0.91		0.91		0.94		0.92		0.84
59.09" - 70.87" (1.501 - 1.800 mm)		0.75		0.80		0.77		0.77		0.80		0.78		0.71

Solid Beech:


Lightly steamed | Homogenously dried to 7-9 % KD | Calibrated thickness |  
Cut-to-size after kiln drying

Tolerances:

Thickness: approx. ± 0.012" |  
Width: approx. ± 0.02" | Length: approx. ± 0.012"/linear ft  
Tolerances refer to a moisture content of 7-9% (solid beech lumber). The swelling and shrinking behavior of higher equilibrium moisture contents must be taken into account.

\* Available only in grading CCC.


Customized lengths are available upon request for orders of 7.6 mbf volume or more per dimension.



width length	1.77" (45 mm)		2.12" (54 mm)		2.67" (68 mm)		3.15" (80 mm)		3.93" (100 mm)		4.92" (125 mm)	
	Pieces	Vol. [mbf]	Pieces	Vol. [mbf]	Pieces	Vol. [mbf]						
<b>COMPONENTS</b>												
118.11" (3,000 mm)	672	1.46	560	1.46	448	1.48	392	1.52	280	1.34	224	1.36*
108.26" (2,750 mm)		1.34		1.34		1.35		1.39		1.24		1.24
94.48" (2,400 mm)		1.17		1.17		1.18		1.22		1.09		1.09
88.58" (2,250 mm)		1.10		1.10		1.11		1.14		1.02		1.02
86.61" (2,200 mm)		1.07		1.07		1.08		1.11		0.99		0.99
82.67" (2,100 mm)		1.03		1.03		1.03		1.06		0.95		0.95
78.74" (2,000 mm)		0.98		0.98		0.98		1.01		0.90		0.90
74.80" (1,900 mm)		0.93		0.93		0.94		0.96		0.86		0.86
70.86" (1,800 mm)		0.88		0.88		0.89		0.91		0.81		0.81
62.99" (1,600 mm)		0.78		0.78		0.79		0.81		0.72		0.72
59.05" (1,500 mm)		0.73		0.73		0.74		0.76		0.68		0.68
55.11" (1,400 mm)		0.68		0.68		0.69		0.71		0.63		0.63
51.18" (1,300 mm)		0.64		0.64		0.64		0.66		0.59		0.59
47.24" (1,200 mm)		0.59		0.59		0.59		0.61		0.54		0.54
39.37" (1,000 mm)		0.49		0.49		0.49		0.51		0.45		0.45
35.43" (900 mm)		0.44		0.44		0.44		0.46		0.41		0.41
31.49" (800 mm)		0.39		0.39		0.39		0.41		0.36		0.36
29.52" (750 mm)		0.37		0.37		0.37		0.38		0.34		0.34
27.55" (700 mm)		0.34		0.34		0.34		0.35		0.32		0.32
25.59" (650 mm)		0.32		0.32		0.32		0.33		0.29		0.29
23.62" (600 mm)	0.29	0.29	0.30	0.30	0.27	0.27						
21.65" (550 mm)	1,344	0.54	1,120	0.54	896	0.54	784	0.56	560	0.50	448	0.50
19.68" (500 mm)		0.49		0.49		0.49		0.51		0.45		0.45
17.71" (450 mm)		0.44		0.44		0.44		0.46		0.41		0.41
15.74" (400 mm)		0.39		0.39		0.39		0.41		0.36		0.36
13.77" (350 mm)		0.34		0.34		0.34		0.35		0.32		0.32
11.81" (300 mm)	2,016	0.44	1,680	0.44	1,344	0.44	1,176	0.46	840	0.41	672	0.41
9.84" (250 mm)		0.37		0.37		0.37		0.38		0.34		0.34
7.87" (200 mm)		0.39		0.39		0.39		0.41		0.36		0.36
5.91" (150 mm)	3,360	0.37	2,800	0.37	2,240	0.37	1,960	0.38	1,400	0.34	1,120	0.34

COMPONENTS SORTED-TO-LENGTHS

106.34" - 118.11" (2,701 - 3,000 mm)	672	1.36	560	1.36	448	1.37	392	1.41	308	1.38	224	1.26
94.53" - 106.30" (2,401 - 2,700 mm)		1.21		1.21		1.22		1.26		1.24		1.12
82.72" - 94.49" (2,101 - 2,400 mm)		1.07		1.07		1.08		1.11		1.09		0.99
70.91" - 82.67" (1,801 - 2,100 mm)		0.93		0.93		0.94		0.96		0.95		0.86
59.09" - 70.87" (1,501 - 1,800 mm)		0.79		0.79		0.79		0.82		0.80		0.73



Solid Beech:

Tolerances:

Lightly steamed | Homogenously dried to 7-9 % KD | Calibrated thickness |  
Cut-to-size after kiln drying

Thickness: approx. ± 0.012" |  
Width: approx. ± 0.02" | Length: approx. ± 0.012"/linear ft

Tolerances refer to a moisture content of 7-9% (solid beech lumber). The swelling and shrinking behavior of higher equilibrium moisture contents must be taken into account.


\* Available only in grading CCC.

Customized lengths are available upon request for orders of 7.6 mbf volume or more per dimension.

width length	1.92" (49 mm)		2.67" (68 mm)		3.15" (80 mm)		3.93" (100 mm)		4.92" (125 mm)	
	Pieces	Vol. [mbf]	Pieces	Vol. [mbf]	Pieces	Vol. [mbf]	Pieces	Vol. [mbf]	Pieces	Vol. [mbf]
<b>COMPONENTS</b>										
118.11" (3,000 mm)	440	1.39	320	1.41	280	1.45	200	1.29	160	1.29*
108.26" (2,750 mm)		1.28		1.29		1.33		1.18		1.18
94.48" (2,400 mm)		1.11		1.12		1.16		1.03		1.03
88.58" (2,250 mm)		1.05		1.05		1.09		0.97		0.97
86.61" (2,200 mm)		1.02		1.03		1.06		0.95		0.95
82.67" (2,100 mm)		0.98		0.98		1.01		0.90		0.90
78.74" (2,000 mm)		0.93		0.94		0.97		0.86		0.86
74.80" (1,900 mm)		0.88		0.89		0.92		0.82		0.82
70.86" (1,800 mm)		0.84		0.84		0.87		0.78		0.78
62.99" (1,600 mm)		0.74		0.75		0.77		0.69		0.69
59.05" (1,500 mm)		0.70		0.70		0.72		0.65		0.65
55.11" (1,400 mm)		0.65		0.66		0.68		0.60		0.60
51.18" (1,300 mm)		0.60		0.61		0.63		0.56		0.56
47.24" (1,200 mm)		0.56		0.56		0.58		0.52		0.52
39.37" (1,000 mm)		0.46		0.47		0.48		0.43		0.43
35.43" (900 mm)		0.42		0.42		0.43		0.39		0.39
31.49" (800 mm)		0.37		0.38		0.39		0.34		0.34
29.52" (750 mm)		0.35		0.35		0.36		0.32		0.32
27.55" (700 mm)		0.33		0.33		0.34		0.30		0.30
25.59" (650 mm)		0.30		0.30		0.31		0.28		0.28
23.62" (600 mm)	0.28	0.28	0.29	0.26	0.26					
21.65" (550 mm)	880	0.51	640	0.52	560	0.53	400	0.47	320	0.47
19.68" (500 mm)		0.46		0.47		0.48		0.43		0.43
17.71" (450 mm)		0.42		0.42		0.43		0.39		0.39
15.74" (400 mm)		0.37		0.38		0.47		0.34		0.34
13.77" (350 mm)		0.33		0.33		0.34		0.30		0.30
11.81" (300 mm)	1,320	0.42	960	0.42	840	0.43	600	0.39	480	0.39
9.84" (250 mm)		0.35		0.35		0.36		0.32		0.32
7.87" (200 mm)		1,760		0.37		1,280		0.38		1,120
5.91" (150 mm)	2,200	0.35	1,600	0.35	1,400	0.36	1,000	0.32	800	0.32

COMPONENTS SORTED-TO-LENGTHS

106.34" - 118.11" (2,701 - 3,000 mm)	440	1.32	320	1.34	280	1.38	200	1.23	224	1.23
94.53" - 106.30" (2,401 - 2,700 mm)		1.18		1.20		1.23		1.10		1.10
82.72" - 94.49" (2,101 - 2,400 mm)		1.05		1.05		1.09		0.97		0.97
70.91" - 82.67" (1,801 - 2,100 mm)		0.91		0.91		0.94		0.84		0.84
59.09" - 70.87" (1,501 - 1,800 mm)		0.77		0.77		0.80		0.71		0.73



Solid Beech:

Tolerances:

Lightly steamed | Homogenously dried to 7-9 % KD | Calibrated thickness |  
Cut-to-size after kiln drying

Thickness: approx. ± 0.012" |  
Width: approx. ± 0.02" | Length: approx. ± 0.012"/linear ft

Tolerances refer to a moisture content of 7-9% (solid beech lumber). The swelling and shrinking behavior of higher equilibrium moisture contents must be taken into account.

\* Available only in grading CCC.

Customized lengths are available upon request for orders of 7.6 mbf volume or more per dimension.